

# ASR1101A ASR1101A-D

## RFID Reader



### Features

- Wiegand26/34 bits RS-485 protocol
- 13.56MHz(Mifare)
- 125KHz(EM-ID)
- Red and Green LEDs
- Sensitive touch keypad with blue backlight
- Watch dog function ensure device free from halting
- Beep Buzzer and LED indicator
- Surface mounted installation



### Technical Specification

Mode	ASR1101A	ASR1101A-D
------	----------	------------

#### System

Main Processor	8 Bit	
----------------	-------	--

#### Read

Read Format	13.56MHz	125KHz
-------------	----------	--------

Read Range	6-8cm (max.)	
------------	--------------	--

Reading time	<0.1s	
--------------	-------	--

#### Function

Tamper Alarm	Yes	
--------------	-----	--

#### Interface

To Controller	RS485, Wiegand26/34	
---------------	---------------------	--

#### General

Keypad	12Keys(0-9,*,#)	
--------	-----------------	--

Sensitive touch keypad	Blue backlight	
------------------------	----------------	--

Beep Tone	Buzzer	
-----------	--------	--

Ingress protection	IP55	
--------------------	------	--

Power Supply	9-15VDC/100mA	
--------------	---------------	--

Working Environment	-30°C~+60°C	
---------------------	-------------	--

Working Humidity	≤95%	
------------------	------	--

Dimension(WxDxH)	87mm*13mm*136mm	
------------------	-----------------	--

Weight	0.25Kg	
--------	--------	--

### Dimensions

